



Intel® PRO/10GbE CX4 Server Adapter

10 Gigabit Performance for Short-distance CX4 Copper

- 10 Gigabit performance in CX4 cable lengths up to 15-25 meters
- Cost-effective, high-speed network connection with low latency
- 64-bit Peripheral Component Interconnect Extended (PCI-X*) interface running up to 133 MHz



Connectivity You Can Count On

The Intel® PRO/10GbE CX4 Server Adapter—part of the second-generation 10-Gigabit Ethernet (10GbE) adapters from Intel—represents the first 10GbE-over-copper connection from Intel. It provides enterprises with a highly affordable, low-latency 10GbE network connection for CX4 cable distances ranging up to 25 meters, depending on wire gauge. This makes the Intel PRO/10GbE CX4 Server Adapter an ideal solution for high-bandwidth network connections in high-performance computing clusters and for short distances within wiring closets.

Built around the highly integrated Intel® 82597EX 10-Gigabit Ethernet Controller for 64-bit PCI-X connections running up to 133 MHz, the Intel PRO/10GbE CX4 Server Adapter is ideal for bandwidth-intensive applications. High-speed server connectivity—once reserved for costly, proprietary technologies such as high-performance computing clusters and grid-based computing—can now be achieved with the standardized connectivity of the Intel PRO/10GbE CX4 Server Adapter. Wide testing for interoperability with switches from major original equipment manufacturers further helps to ensure that the Intel PRO/10GbE CX4 Server Adapter will provide connectivity you can count on.

The Intel PRO/10GbE CX4 Server Adapter helps improve network productivity and eliminate costly proprietary networking topologies while enabling deployment of standards-compliant Ethernet connectivity based on the IEEE 802.3ak 10 Gigabit Ethernet standard for CX4 copper cable.

10GBASE-CX4 Applications and Advantages

The Intel PRO/10GbE CX4 Server Adapter is an immediate, lower-cost solution for a wide range of data-center applications, including:

- High-performance computing clusters
- Consolidated LAN and iSCSI traffic
- Database link to backup storage and NAS
- Digital editing, scientific and commercial simulation, and collaboration
- Scaled-up consolidated servers
- Real-time video streaming on web servers

By using the Intel PRO/10GbE CX4 Server Adapter on critical server and storage applications, you can:

- Increase performance and bandwidth
- Consolidate multiple GbE connections
- Improve video streaming
- Scale up by consolidating servers
- Converge your networks by combining LAN and storage traffic
- Enable low-cost HPC clusters with low-cost, high-bandwidth interconnects

Features

Features	Benefits
Intel® 82597EX 10GbE PCI-X* 133-MHz, 64-bit media access control (MAC) controller CX4 copper cable support through CX4 XPAK module	<ul style="list-style-type: none">• High performance on widely adopted second-generation PCI host-bus interface• Allows 10GbE connectivity over CX4 copper cable lengths up to 25 m, depending on American Wire Gauge (AWG) cable ratings
IEEE 802.3ak* 10GBASE CX4 compliant	<ul style="list-style-type: none">• Supports industry-wide 10 Gigabit Ethernet standard
Jumbo frames supported up to 16 KB	<ul style="list-style-type: none">• Increases performance through reduced overhead
Transmission control protocol/Internet protocol (TCP/IP) segmentation and TCP checksum offload in receive (Rx) and transmit (Tx)	<ul style="list-style-type: none">• Provides efficiency for host processing
256 KB Rx and 32 KB Tx data first-in, first-out (FIFO) buffer	<ul style="list-style-type: none">• Enhanced Tx and Rx logic with minimum buffer requirements
Parity protection for Rx FIFO buffer	<ul style="list-style-type: none">• Data integrity
Mechanisms for delaying/reducing Tx and Rx frame interrupts	<ul style="list-style-type: none">• Reduces processor utilization
PCI-X 1.0a and PCI 2.3	<ul style="list-style-type: none">• Wide compatibility
Flow control 802.3x*	<ul style="list-style-type: none">• Supports industry-wide networking standard
PCI 2.2 message signaled interrupts	<ul style="list-style-type: none">• Improves system interrupt handling
Intel® PROSet Utility for Microsoft® Device Manager	<ul style="list-style-type: none">• Provides point-and-click power over individual adapters, advanced adapter features, connection teaming, and virtual local area network (VLAN) configuration
Built on Intel® lead-free ¹ technology for RoHS ² compliance	<ul style="list-style-type: none">• Compliant with the new European Union directive (effective July 2006) to reduce the use of hazardous materials

Order Code

PXLA8591CX4 (Single Pack)

Companion Products

Consider these Intel® products in your server and network planning:

- Intel® PRO/1000 Server Adapters
 - Copper or fiber-optic network connectivity, up to four ports per card
 - Solutions for PCI Express, PCI-X, and PCI interfaces
- Intel® PRO/10GbE Server Adapters
 - Short-range and long-range connectivity solutions for fiber-optic cabling
- Intel® PRO/1000 Desktop Adapters for PCI Express and PCI interfaces
- Other Intel® PRO Desktop and Server Adapters
- Intel® Xeon™ processors
- Intel® Itanium® processors
- Intel® Server Boards

Benefits

Network-Ready PCs

Top PC and server manufacturers offer Intel® adapters in their new products. Specify or ask for Intel® PRO Network Connections with your next PC, server, or mobile PC purchase. For a list of preferred suppliers, visit us at www.intel.com/network/connectivity/how_to_buy/index.htm.

Customer Support

Intel® Customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at <http://support.intel.com/support/network>. Service and availability may vary by country.

For Product Information

To speak to a customer service representative regarding Intel products, please call 1-800-538-3373 (U.S. and Canada) or visit www.intel.com/support/9089.htm for the telephone number in your area. For additional product information on Intel® Networking and Communication products, visit www.intel.com/network/connectivity.

Specifications: Intel® PRO/10GbE CX4 Server Adapter

General

Product code	PXLA8591CX4
Connector	CX4 XPAK module
IEEE standards/network topology	10GBASE CX4
Wiring	CX4 cable

Adapter Product Features

Plug and Play specification support	•
Easy installation with Intel® PROSet Utility and Intel® PRO Intelligent Install	•
RoHS compliant ²	•
Auto-negotiation, full-duplex capable	•
Cable distance	To 25 meters, depending on cable gauge and parameters (AWG 24, 20 m; AWG 26, 15 m; AWG 28, 11 m)

Network Management

Wired for Management (WfM) baseline v2.0 enabled for servers	•
Desktop Management Interface (DMI) 2.0 support, Windows Management Instrumentation (WMI), and Simple Network Management Protocol (SNMP)-manageable	•
Advanced configuration and power interface (ACPI) 1.0 power management	•
Preboot execution environment (PXE)—enabled through boot read-only memory (ROM)	•

Network Operating Systems (NOS) Software Support

Microsoft Windows* 2000 (Server, Advanced Server, Datacenter Server), Server 2003	•
Linux* 2.4, 2.6	•
FreeBSD 5.3 kernel	•

Intel Backing

Limited lifetime warranty	•
90-day, money-back guarantee (U.S. and Canada)	•

Advanced Software Features

Adapter fault tolerance (AFT)	•
Switch fault tolerance (SFT)	•
Adaptive load balancing (ALB)	•
Fast EtherChannel* ³ (FEC)	•
Gigabit EtherChannel* ³ (GEC)	•
Teaming support	•
Multiple teams	•
Test switch configuration	Tested with major switch original equipment manufacturers (OEMs)
Jumbo frames (up to 16 KB)	•
IEEE 802.1Q* VLANs	•
IEEE 802.3* support	•
TCP checksum offload (Rx/Tx TCP, IPv4)	•
On now/instantly available PCI initiative	•
TCP segmentation/large send offload	•
Interrupt moderation	•

Technical Features

Throughput performance	5-7 Gbps full-duplex Ethernet performance
Bus type	PCI-X* 1.0, PCI local bus interface 2.3
Bus width	32- and 64-bit
Bus mastering	•
Bus speed (MHz)	33, 66, and 133 MHz
Plug and play support	•
PCI hot plug/active PCI	•
Hardware certifications	FCC Class A, UL, CE, VCCI, BSMI, CTICK, MIC
Controller-processor	Intel® 82597EX Controller
Typical power consumption	<10 W (5 V main, 3.3 V main)
Operating temperature	0–55° C
LEDs	4 (green): Tx, Rx, link, port identify

Physical Dimensions

Length	16.8 cm (6.6 in)
Width	10.7 cm (4.2 in)

For additional information on the Intel® PRO/10GbE CX4 Server Adapter and Intel's complete line of 10GbE adapters, visit www.intel.com/network/connectivity/products/10GbE.htm

¹Lead has not been intentionally added, but lead may still exist as an impurity below 1000 ppm, or an approved RoHS exemption applies.

²Lead and other materials banned in the RoHS Directive are either (1) below all applicable substance thresholds as proposed by the EU or (2) an approved/pending exemption applies.

³Available only when used with a capable switch.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. Intel products are not intended for use in medical, life saving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

*Other names and brands may be claimed as the property of others.

Copyright © 2005 Intel Corporation. All rights reserved.

Intel, the Intel logo, Intel Xeon, and Intel Itanium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

